

PANIC LOCK SLIDING DEAD BOLT, 85 mm BETWEEN AXES
615E, 612E RANGE

CHARACTERISTIC

- Panic lock for aluminium and steel doors
- Reversible panic mechanism
- 22mm SS front plate
- 11mm reversible latch bolt
- Adjustable latch bolt, except in 25mm entrance
- 15 mm box
- 8mm square ruler
- **Operated by key and knob or pull handle from outside. The key blocks or unblocks the handle**
- Cylinder set screw
- 85mm between axes (615E) or 92mm (612E)
- Fire-proof lock

VERSIONS

- Different width and type of frontplate available


OPTIONAL ACCESSORIES

- Complete range of **strike plates**
- Complete range of **cylinders**

DESCRIPTION	REF.	MEASUREMENTS		CAM	FINISH		UNITS
		B	A		FRONT PLATE	CYLINDER	

- Latch bolt and dead bolt
- Cylinder not included
- Lock with nut

- **Strike plate options**
- **Electric strike plate option**



615E/25/6	22	37	15	Al	1	20
615E/30/6	27	42	15	Al	1	20
615E/35/6	32	47	15	Al	1	20
612E/25/6	22	37	15	Al	1	20
612E/30/6	27	42	15	Al	1	20
612E/35/6	32	47	15	Al	1	20

